

Home Standby - 15

Home Standby - 20

Liquid Cooled Gas Engine Generator Sets

Continuous Standby Power Rating

15kW 60 Hz

20kW 60 Hz

Prime Power Rating

11kW 60 Hz

15kW 60 Hz



Models:

04721 (15kW/Single Phase NG or LPV)

04722 (15kW/Single Phase NG or LPV)

04723 (20kW/Single Phase NG or LPV)

04724 (20kW/Single Phase NG or LPV)

UL 2200 Listed

Power Matched

GENERAC MMC 4G15 ENGINE

Naturally Aspirated

Generac

100 Amp Automatic

Transfer Switch (UL Listed)

Included with Models 04721
& 04723. Available for models

04722 & 04724

2 Year Limited Warranty

FEATURES

- INNOVATIVE DESIGN & PROTOTYPE TESTING** are key components of GENERAC'S success in "IMPROVING POWER BY DESIGN." But it doesn't stop there. Total commitment to component testing, reliability testing, environmental testing, destruction and life testing, plus testing to applicable CSA, NEMA, EGSA, and other standards, allows you to choose GENERAC POWER SYSTEMS with the confidence that these systems will provide superior performance.
- TEST CRITERIA:**
 - ✓ **PROTOTYPE TESTED**
 - ✓ **SYSTEM TORSIONAL TESTED**
 - ✓ **ELECTRO-MAGNETIC INTERFERENCE**
 - ✓ **NEMA MG1-22 EVALUATION**
 - ✓ **MOTOR STARTING ABILITY**
- SOLID-STATE, FREQUENCY COMPENSATED VOLTAGE REGULATION.** This state-of-the-art power maximizing regulation system is standard on all Generac models. It provides optimized FAST RESPONSE to changing load conditions and MAXIMUM MOTOR STARTING CAPABILITY by electronically torque-matching the surge loads to the engine.
- SINGLE SOURCE SERVICE RESPONSE** from Generac's dealer network provides parts and service know-how for the entire unit, from the engine to the smallest electronic component. You are never on your own when you own a GENERAC POWER SYSTEM.
- GENERAC TRANSFER SWITCHES.** Long life and reliability are synonymous with GENERAC POWER SYSTEMS. One reason for this confidence is that the GENERAC product line includes its own transfer systems and controls for total system compatibility.



APPLICATION & ENGINEERING DATA

GENERATOR SPECIFICATIONS

TYPE Home Standby 15	Four-pole, revolving field
TYPE Home Standby 20	Two-pole, revolving field
ROTOR INSULATION	Class F
STATOR INSULATION	Class F
VOLTAGE WAVE FORM DEVIATION	<5%
TOTAL HARMONIC DISTORTION (line to line)	<5%
TELEPHONE INTERFERENCE FACTOR (TIF)	<50
ALTERNATOR	Self-ventilated and drip-proof
BEARINGS (PRE-LUBED & SEALED)	1
COUPLING	Direct, Flexible Disc
LOAD CAPACITY (STANDBY)	100%

NOTE: Emergency loading in compliance with NFPA 99, NFPA 110, paragraph 5-13.2.6. Generator rating and performance in accordance with ISO8528-5, BS5514, SAE J1349, ISO3046, and DIN6271 standards.

EXCITATION SYSTEM

DIRECT	DC excitation system ✓
	Low-velocity brushes and slip rings ✓
REGULATION	Solid-state ✓
	±1% regulation ✓

GENERATOR FEATURES

- Two/Four pole, revolving field generator, directly connected to the engine shaft through a heavy-duty, flexible disc for permanent alignment.
- Generator meets temperature rise standards for class "F" insulation as defined by NEMA MG1-22.
- Stator windings are "trickle" varnished and rotor windings are "roll-dipped" for complete Class H impregnation.
- Unit tested for motorstarting ability by measuring instantaneous voltage dip with a waveform data acquisition system.
- All models utilize an advanced wire harness design for reliable interconnection within the circuitry.
- Magnetic circuit, including amortisseur windings, tooth and skewed stator design, provides a minimal level of waveform distortion and an electromagnetic interference level which meets accepted requirements for standard AM radio, TV, and marine radio telephone applications.
- Voltage waveform deviation, total harmonic content of the AC waveform, and balanced T.I.F. (Telephone Influence Factor) have been evaluated to acceptable standards in accordance with NEMA MG1-22.
- Alternator is of drip-proof guarded construction.
- Fully life-tested protective systems, including "field circuit and thermal overload protection" and standard mainline circuit breakers capable of handling full output capacity.
- System torsional acceptability confirmed during prototype testing.

Rating definitions - Standby: Applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. (All ratings in accordance with BS5514, ISO3046 and DIN6271). Prime (Unlimited Running Time): Applicable for supplying electric power in lieu of commercially purchased power. Prime power is the maximum power available at variable load. A 10% overload capacity is available for 1 hour in 12 hours. (All ratings in accordance with BS5514, ISO3046, ISO8528 and DIN6271).

ENGINE SPECIFICATIONS

MAKE	GENERAC
MODEL	MMC 4G15
CYLINDERS	4 in-line
DISPLACEMENT	1.5 Liter (91.5 cu. in.)
BORE	75.5 mm (2.97 in.)
STROKE	82 mm (3.23 in.)
COMPRESSION RATIO	9:4:1
INTAKE AIR	Naturally Aspirated
NUMBER OF MAIN BEARINGS	5
CONNECTING RODS	4-Drop forged steel
CYLINDER HEAD	S.O.H.C.
PISTONS	4-Aluminum Alloy
CRANKSHAFT	Drop Forged Steel

VALVE TRAIN

LIFTER TYPE	Rocker Arm Type
INTAKE VALVE MATERIAL	High Temperature Alloy Forged
EXHAUST VALVE MATERIAL	High Temperature Alloy Forged
VALVE SEATS	Replaceable

ENGINE GOVERNOR

<input type="checkbox"/> ELECTRONIC.....	Standard
FREQUENCY REGULATION, NO-LOAD TO FULL LOAD	0.5%
STEADY STATE REGULATION	±0.25%

LUBRICATION SYSTEM

TYPE OF OIL PUMP	Gear
OIL FILTER	Full flow, cartridge
CRANKCASE CAPACITY	3.8 Liters (4 qts.)

COOLING SYSTEM

TYPE OF SYSTEM	Pressurized, closed recovery
WATER PUMP	Pre-lubed, self-sealing
TYPE OF FAN	Pusher
NUMBER OF FAN BLADES	6
DIAMETER OF FAN	380 mm (15.0 in.)
COOLANT HEATER	500 W

FUEL SYSTEM

FUEL	
<input type="checkbox"/> Natural Gas or L.P. Vapor	Standard
CARBURETOR	Down draft
SECONDARY FUEL REGULATOR. Nat. Gas or L.P. Vapor Systems	
AUTOMATIC FUEL LOCKOFF SOLENOID	Standard
OPERATING FUEL PRESSURE VAPOR SYSTEMS	11" to 14" H ₂ O

ELECTRICAL SYSTEM

BATTERY CHARGE ALTERNATOR	15 Amps at 12 V
STARTER MOTOR	12 V
RECOMMENDED BATTERY	12 V, 525 CCA @ 0° F/75 A.H., 26R
GROUND POLARITY	Negative

Home Standby - 15
Home Standby - 20



OPERATING DATA

	STANDBY				PRIME			
	Home Standby-15		Home Standby-20		Home Standby-15		Home Standby-20	
	N.G./L.P.	Rated AMP	N.G./L.P.	Rated AMP	N.G./L.P.	Rated AMP	N.G./L.P.	Rated AMP
GENERATOR OUTPUT VOLTAGE/KW - 60Hz 120/240V, 1-phase, 1.0 pf	15	62.5	20	83.3	11	45.8	15	62.5
MOTORSTARTING Maximum at 35% instantaneous voltage dip with standard alternator; 60 Hz	28 KVA		39 KVA		28 KVA		39 KVA	
FUEL Fuel consumption - 60 Hz--100% Load ft. ³ /hr.(gal./hr.) m ³ /hr.	N.G.	L.P.	N.G.	L.P.	N.G.	L.P.	N.G.	L.P.
	265 7.5	110 (3.0) 3.1	369 10.4	153 (4.2) 4.3	204 5.8	85 (2.3) 2.4	301 8.5	125 (3.4) 3.5
COOLING								
Coolant capacity	System lit.(US gal.)	7.5 (2)	7.5 (2)	7.5 (2)	7.5 (2)	7.5 (2)	7.5 (2)	7.5 (2)
	Engine lit.(US gal.)	0.9 (0.25)	0.9 (0.25)	0.9 (0.25)	0.9 (0.25)	0.9 (0.25)	0.9 (0.25)	0.9 (0.25)
	Radiator lit.(US gal.)	6.6 (1.75)	6.6 (1.75)	6.6 (1.75)	6.6 (1.75)	6.6 (1.75)	6.6 (1.75)	6.6 (1.75)
Coolant flow/min.	60 Hz lit.(US gal.)	25 (6.6)	40 (10.6)	40 (10.6)	25 (6.6)	40 (10.6)	40 (10.6)	40 (10.6)
Heat rejection to coolant	60 Hz BTU/hr.	72,000	96,000	96,000	53,000	77,000	77,000	77,000
Cooling air flow	60 Hz m ³ /min. (cfm)	40 (883)	45 (1590)	45 (1590)	40 (883)	45 (1590)	45 (1590)	45 (1590)
COMBUSTION AIR REQUIREMENTS Flow at rated power 60 Hz m ³ /min. (cfm)	1.2 (41)		1.6 (57)		0.9 (32)		1.3 (47)	
EXHAUST								
Exhaust flow at rated output 60 Hz m ³ /min. (cfm)	3.9 (137)		6.0 (212)		3.0 (105)		4.9 (173)	
Max. recommended back pressure Kpa (Hg)	5.0 (1.5")		5.0 (1.5")		5.0 (1.5")		5.0 (1.5")	
Exhaust temp. at rated output °C (°F)	621 (1150)		704 (1300)		593 (1100)		677 (1250)	
Exhaust outlet size N.P.T. (female)	1.5"		1.5"		1.5"		1.5"	
ENGINE								
Rated at RPM	60 Hz	1800	3600	3600	1800	3600	3600	3600
HP at rated KW	60 Hz	24	32	32	17	26	26	26
Piston speed	60 Hz m/min. (ft./min.)	295 (969)	590 (1937)	590 (1937)	295 (969)	590 (1937)	590 (1937)	590 (1937)
BMEP	60 Hz	116	78	78	85	62	62	62
POWER ADJUSTMENT FOR AMBIENT CONDITIONS								
Temperature								
	-3% for every 10°C above - °C	25	25	25	25	25	25	25
	-1.5% for every 10°F above - °F	77	77	77	77	77	77	77
Altitude								
	-3% for every 300 m above - m	913	913	913	913	913	913	913
	-3% for every 1000 ft. above - ft.	3000	3000	3000	3000	3000	3000	3000

TRANSFER SWITCH SPECIFICATIONS (If so equipped)		
No. of Poles		2
Current Rating	(amps)	100
Voltage Rating	(VAC)	250
Utility Voltage Monitor	(fixed)	
	Pick-up	80%
Enclosure - NEMA 1		Standard
Dropout		60%
Return to Utility		1 minute
Exerciser 7 minute weekly		Standard
UL Listed		Standard
Dimensions	(H" x W" x D")	20 x 15 x 6
Weight		25 lbs.

STANDARD ENGINE & SAFETY FEATURES

Home Standby - 15

Home Standby - 20



- | | |
|---|--|
| <ul style="list-style-type: none"> <input type="checkbox"/> High Coolant Temperature Automatic Shutdown <input type="checkbox"/> Low Coolant Level Automatic Shutdown <input type="checkbox"/> Low Oil Pressure Automatic Shutdown <input type="checkbox"/> Overspeed Automatic Shutdown (Solid-state) <input type="checkbox"/> Crank Limiter (Solid-state) <input type="checkbox"/> Oil Drain Extension <input type="checkbox"/> Radiator Drain Extension <input type="checkbox"/> Factory-Installed Cool Flow Radiator <input type="checkbox"/> Closed Coolant Recovery System <input type="checkbox"/> Engine Block Heater <input type="checkbox"/> Rubber-Booted Engine Electrical Connections <input type="checkbox"/> Fuel Lockoff Solenoid <input type="checkbox"/> Isochronous Governor <input type="checkbox"/> Secondary Fuel Regulator (N.G. and L.P.) <input type="checkbox"/> Weather Protective Enclosure (Locking Type) | <ul style="list-style-type: none"> <input type="checkbox"/> Battery Charge Alternator <input type="checkbox"/> Battery Cables <input type="checkbox"/> Battery Tray <input type="checkbox"/> Vibration Isolation of Unit to Mounting Base <input type="checkbox"/> 12 Volt, Solenoid-Activated Starter Motor <input type="checkbox"/> Air Cleaner <input type="checkbox"/> Fan Guard <input type="checkbox"/> Control Console <input type="checkbox"/> UV/Ozone Resistant Hoses <input type="checkbox"/> Stainless Steel Flexible Exhaust Connection <input type="checkbox"/> Flexible Fuel Line <input type="checkbox"/> Critical Exhaust Silencer <input type="checkbox"/> Battery Trickle Charger <input type="checkbox"/> Main Line Circuit Breaker <input type="checkbox"/> Automatic Transfer Switch <p>(Included with models 04721 & 04723 only)</p> |
|---|--|

Home Standby Control Features:

Home Standby Control Console
 Manual/Auto/Off switch
 Hour meter
 Fault indicator lamp
 Fuse (panel overload)
 Set exercise time switch

Home Standby Microprocessor Controls
 Automatic voltage regulation
 Utility voltage sensing
 Utility interrupt delay
 (10-second setpoint)
 Engine warm-up
 (10-second setpoint)
 Engine cool-down
 (1-minute setpoint)
 Seven-day exerciser

Distributed by:

